



PPV VERTEC POLYURETHANE FILM PRODUCT INFORMATION

Technical Datasheet

LAYOUT

POLYETHYLENE COVERSHEET
POLYURETHANE (PU) VERTEC ELASTOMER
POLYESTER SUBSTRATE

1.0 +/- 0.1 mils

See PU Film Thickness Table

3.0 +/- 0.1 mils

PU Vertec Film Tack Thickness Table

Tack level	1.5mil	6.0mil
EH02	X	X
EH04	X	X
EH06	X	X

PU Vertec Material Thickness Specification

PU VERTEC Film Material	Nominal Thickness (PU Vertec)	Nominal Working Thickness (PU Vertec +Substrate)
1.5 mil	1.5 mils +/- 0.5	4.5 mils +/- 0.6
6.0 mil	6.0 mil +/- 0.7	9.0 mil +/- 0.8

NOTES

1. The Vertec PU material on PPV film is easily separated from the Polyester Substrate as there is no bonding agent between the Vertec PU material and substrate.
2. Above information is preliminary and is subject to change.

ENVIRONMENTAL COMPATIBILITY

- Operating Temperature (PU Only): -10°C to +35°C.
- Shipping/Storage Temperature: -10°C to 50°C
- Shelf Life: Minimum 2 years

GEL-PAK

31398 Huntwood Avenue, Hayward, CA 94544

Toll-Free 888-621-4147 **Phone** 510-576-2220 **Fax** 510-576-2282

Website www.gelpak.com

Division of

DELPHON