



## PPV VERTEC POLYURETHANE FILM PRODUCT INFORMATION (**PRELIMINARY**)

### Technical Datasheet

#### LAYOUT

POLYETHYLENE COVERSHEET	1.0 +/- 0.1 mils
POLYURETHANE MATERIAL	See PU Film Thickness Table
POLYESTER SUBSTRATE	3.0 +/- 0.1 mils

Vertec PU Film Tack Thickness Table

Tack level	1.5mil	6.0mil
<b>EH02</b>	X	X
<b>EH04</b>	X	X
<b>EH06</b>		X

Vertec Material Thickness Specification

VERTEC PU Film Material	Nominal Vertec PU Film Thickness
<b>1.5 mil</b>	1.5 mils +/- 0.5
<b>6.0 mil</b>	6.0 mil +/- 0.7

#### NOTES

1. The Vertec PU material on PPV film is easily separated from the Polyester Substrate as there is no bonding agent between the Vertec PU material and substrate.
2. Above information is preliminary and is subject to change.

#### ENVIRONMENTAL COMPATIBILITY

- Operating Temperature (PU Only): -10°C to +35°C.
- Storage: Minimum 2 years at 21°C and 50% RH.

#### GEL-PAK

31398 Huntwood Avenue, Hayward, CA 94544  
**Toll-Free** 888-621-4147 **Phone** 510-576-2220 **Fax** 510-576-2282  
**Website** [www.gelpak.com](http://www.gelpak.com)

Division of

# DELPHON